



SPOT TAPE ENCI082

Spot tape for twisted cables

Our innovative spot taping machine redefines standards with a cycle time of 3.5 seconds, standing out for its adaptability and precision. The state-of-the-art touchscreen streamlines tape length adjustment, providing total control. Its exceptional versatility allows working with tapes ranging from 9mm to 19mm without part changes, optimizing various applications. Designed for efficiency and convenience, access and maintenance are straightforward. This machine provides an advanced solution for spot taping.

- User-friendly interface
- Program capacity of up to 1000 programs
- Rubber clamps to prevent cable damage
- Cable tensioning for perfect taping
- Selectable tape length
- Easy maintenance
- Convenient access inside the machine
- Ease of cleaning

Operation

By placing the cables on their respective supports and tightening the levers, the taping process begins, wrapping around the cables. The ENCI08 taping machine loads the tape so that when the cables are released, a new taping cycle can be initiated.

Información Técnica

| | |
|----------------------|---|
| Minimum cable length | 150 mm |
| Cross section | 2 x 0.13 up to 2 x 3 mm ² |
| Length of the ends | 10 – 80 mm |
| PRogram memory | Hasta 1,000 programs |
| Power Supply | 230 VAC +/-5%, 50/60 Hz, <1kw, Air 6 bar (90 psi) |
| Important | Special Spare Parts recomienda que las muestras de cable sean entregadas en casos donde haya duda sobre las capacidades de procesamiento de alguna máquina en particular. |